

It Fits Every Industrial Demand

Beyond Your Imagination



3DWOX 30X

3DWOX 30X



Model	3DWOX 30X	
Technology	FFF	
Type	Dual Nozzle, Direct Printing	
Build Size	740 x 490 x 150 mm	
Print Head	Diameter	0.4 mm (std.), 0.6 & 0.8 mm(optional)
	Max Temp.	280°C
	Printing Speed	Max. 300mm/s (Std. 100mm/s)
Filament	Diameter	1.75 mm
	Spool Quantity	8 Spools (Automatic Switch), Max 3kg each
	Material	PLA, ABS, TPU, PVA, PA(Nylon), PETG, HIPS, PC, ASA, PE and more
Bed	Types	PC Metallic Flexible Bed (optional PI, PEI sheet)
	Max Temp.	90°C
	Leveling	Full Auto Leveling / Active Leveling
GUI	10.1" Full Color Touch Screen	
Printer Size (W x D x H)	1,200x 1,050x1,120* mm (*1,520mm incl. Table)	
Additional Features	Playback Speaker	
	Web Monitoring (PC / Mobile) Wisdom3D (Production Management Solution) (optional)	
	EMO/Reset Switch, Power Failure Safe Dry Box : Dehumidifier (optional)	